

DHI-PHSIA0.9-SS

Indoor Fine Pixel Pitch LED



Features :

- Ultra-thin 25mm and super-light 5.0kg design.
- 16:9 Golden aspect ratio , can easily achieve pixel to pixel 2K,4K,8K,16K resolution.
- CNC die-casting aluminum cabinet, splicing tolerance is controlled within ± 0.1 mm.
- Supports dual backup of power supply and signals (customizable).
- Dot by dot calibration ensures color richness and brightness uniformity.



Technical Specification

Model

Model	DHI-PHSIA0.9-SS
-------	-----------------

Parameters

Pixel Pitch	0.9375mm
Pixel Configuration	1R1G1B
LED Type	IMD 4IN1
Brightness (Max)	500 nit
Color Temperature	2000k ~ 9500K(adjustable)
Viewing Angle	H160° / V140°
Pixel Density	1137,778dots/m ²
Module Size	300mm×168.75mm
Module Resolution	320x180 dots
Cabinet Size	W600mm×H337.5mm×D25mm
Cabinet Resolution (W×H)	640×360 dots
Cabinet Weight	4.5 kg ± 0.5
Cabinet Material	Die-cast Aluminum

Operating Temperature/ Humidity	-20 C~+50 C/10~80%RH
Storage Temperature/ Humidity	-25 C~+60 C/10~80%RH
IP Rating	Front IP30/Rear IP30
Aspect Ratio	16:9
Gray Scale	14 bits
Contrast Ratio	5000:1
Refresh Rate	3840Hz
Input Voltage	AC 110~220V (+/-10%)
Input Power (max)	470 W/m ²
Input Power (Avg)	160 W/m ²
Installation	Wall Mounted/Floor Mounted
Maintenance	Front Maintenance
Lamp Lifespan	≥100,000 H
Signal Transmission Distance	CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km)

Dimensions

